



1. Identification of Substance/ Preparation and Company				
Product Name:	PES-CHEM 506 ALUPRIME ACTIVATOR			
Company: Chemical Name & Synonyms: For Information: In an Emergency:	PLANT EQUIPMENT & SVCS, 5401 HWY 21 W, BRYAN, TX 77803 Modified epoxy Call 979-779-8700 <u>www.pes-solutions.com</u> email: <u>pes1@pes-solutions.com</u> CHEMTREC – 800-424-9300			
2. <u>Hazards Identification</u> Flammable Corrosive Harmful by inhalation Dangerous for the environment 3. Composition/ Informat				
	tion on ingredients		D	
Hazardous Components Xylene (mixed isomers) Complex modified polyamines 51/53		Cas Number 1330-20-7 preparation	Percentage <=5.1% <=9.8%	Classification Xn; R10-20/21-38 Xi;C;N; R20/22-34-36/37/38/R43-50-52-
4. First Aid Measures	Summon immedia	te medical assistar	nce after contact w	ith skin, eyes, inhalation or ingestion
Eye: Skin: Ingestion: Inhalation:	Flush eyes with plenty of water, seek medical advice Remove product and contaminated clothing and wash area with water, seek medical advice. Except in most minor, superficial or localized burns, cover the affected area with a sterile dressing or clean sheeting. DO NOT APPLY GREASES OR OINTMENTS. Drink plenty of water, DO NOT INDUCE VOMITING, and seek medical attention immediately Remove patient to fresh air. If breathing has stopped give assisted respiration. Prevent aspiration of vomit. Turn victims head to one side. Seek medical advice <i>First Aiders should protect themselves from exposure (Ref to section 8)</i>			
5. Fire Fighting Measures				
Extinguishing Media: Exposure Hazards:	 Ignition will give rise to class B Fire, in case of fire use Water sprays, Dry chemical, CO2 or Alcohol foam May generate toxic, irritating or flammable combustion products. Sudden reaction and fire may result if mixed with an oxidizing agent. 			
Fire Fighting Equipment:	Wear Self-contained	breathing apparatus	s, rubber boots, glove	es and body suit
6. <u>Accidental Release Measures</u>				

Avoid contamination of ground and surface waters. Scrape up and transfer into a suitable container. Wash area with water. *Refer to section 5, 8 and 13 for protective Measures and Disposal.*

7. Handling and Storage

Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Avoid breathing vapors. Wash hands after contact. Keep container tightly closed in a cool, well ventilated area. Keep away from oxidizers, heat or flames.

8. Exposure Controls/ Personal Protection

OCCUPATIONAL EXPOSURE LIMITS - 2,2iminodiethylamine WEL-LONG-TERM VALUE - 1ppm, 10mg/ m3

Not required during normal use
Not during normal use
Protective clothing should be worn to avoid skin contact
Safety Goggles

Material Safety Data Sheet



9. Physical/ Chemical Properties

Appearance:	Amber Fluid	Odor:	Ammoniacal, Fishy
Viscosity:	N/A	Specific Gravity:	1.02g/cm3 at 68°F
Boiling Point/ Range:	>392°F	Flammability:	N/D
Flash Point;	186.8°F	Melting Point:	-0.4°F
Auto Flammability:	N/D	Explosive Properties:	Lower: 1.3 vol%
			Upper: 13.0% vol
Oxidizing Properties:	N/D	Vapor Pressure:	0.3hPa at 68°F
Evaporation Rate:	N/D	Solubility:	Insoluble in water
PH:	Alkaline	Partition Coefficient:	N/D

10. Stability and Reactivity

Stability;	Stable
Materials to Avoid:	Oxidizing agents - cleaning solutions. Acids - reaction accompanied by large heat release occurs when the
	product is mixed with acids
Hazardous Decomposition:	Carbon Monoxide, Carbon Dioxide in a fire. Ammonia when heated. Nitrogen Oxides in a fire. Combustion in
	an oxygen starved environment produces toxic products including nitriles and amides
Hazardous Polymerizations:	None

Hazardous Polymenzadons.

11. Toxicological Information

Oral:	Harmful by inhalation or if swallowed
Inhalation:	N/A during normal use
Eye:	Severe irritant. May cause burns
Skin:	Severe Irritant. May cause burns

12. Ecological Information

Do not allow to enter water course. Waste from this product may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

13. Disposal Considerations

In uncured state, dispose as chemical waste in accordance with local regulations. In cured state when mixed correctly with the base component, dispose as solid waste

14. Transport Information

UN No: 2735	Class:	8	P.G:	III	Technical Name: Amine, liquid, corrosive, N.O.S. (m-
phenylenebis(met	hylamine)				

15. Regulatory Information

Labeling:	Corrosive (C), Harmful (Xn),				
	R Phrases	(R34)	Causes Burns		
		(R20/22)	Harmful by inhalation and if swallowed		
		(R43)	May cause sensitization by skin contact		
		(R62)	Possible risk of impaired fertility		
	S Phrases	(S2)	Keep out of reach of children		
		(S26)	In case of contact with eyes, rinse immediately with plenty of water and seek medical		
advices					
		(\$36/37/39)	Wear suitable protective clothing, gloves and eye/face protection		
		(S45)	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)		
advices	S Phrases	(R62) (S2) (S26) (S36/37/39)	Possible risk of impaired fertility Keep out of reach of children In case of contact with eyes, rinse immediately with plenty of water and seek medica Wear suitable protective clothing, gloves and eye/face protection In case of accident or if you feel unwell, seek medical advice immediately (show the		

Material Safety Data Sheet



Regulations: All components of this product are listed on the TSCA Inventory or are exempt from listing

16. Other Information

Risk phrases used in section 3 and not previously mentioned:

R10; flammable. R22; Harmful if swallowed. R21/22; Harmful in contact with skin if swallowed. R36/38; Irritating to skin and eyes. R37; irritating to respiratory system. R41; Risk of serious damage to eyes. R52/53; Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment

The information contained within this document is furnished without warranty of any kind. Users should consider this data only as a supplement of other information gathered by them and make independent determinations of suitability and completeness of information from all sources to ensure proper use and disposal of these materials and the safety of employees and customers.