

# Material Safety Data Sheet



## 1. Identification of Substance/ Preparation and Company

Product Name: **PES-CHEM 505 DAMP SEAL BASE**  
Company: POLYMERIC ENGINEERED SOLUTIONS, 5401 HWY 21 W, BRYAN, TX 77803  
Chemical Name & Synonyms: Modified Epoxy Resin  
For Information: Call 979-779-8700 [www.pes-solutions.com](http://www.pes-solutions.com) email: [pes1@pes-solutions.com](mailto:pes1@pes-solutions.com)  
In an Emergency: As Above

## 2. Hazards Identification

Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

### Signs and Symptoms of Exposure (Acute Effects)

In contact with skin and eyes causes irritation. Can lead to sensitization

### Signs and Symptoms of Exposure (Possible long term effects)

Soreness. Red Skin. Rash. May cause sensitization

## 3. Composition/ Information on Ingredients

Hazardous Components	Cas Number	Percentage	Classification
Bisphenol A/ F Epoxy resin	25068-38-6/ 28064-14-4	50-100%	Xi; R36/38-43-51/53
Alkyl Glycidyl Ether	68609-97-2	5-20%	Xi; R38-43 N; 51/53

## 4. First Aid Measures

*Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion*

**Eye:** Immediately flush eyes with plenty of running water for at least 15 minutes. If irritation persists seek medical advice

**Skin:** Remove contaminated clothing immediately. Wash affected area with soap and water. If irritation persists seek medical attention.

**Ingestion:** Do not induce vomiting. Rinse mouth and drink plenty of water. Seek medical attention

**Inhalation:** Remove person to fresh air.

**FIRST AIDERS SHOULD PROTECT THEMSELVES FROM EXPOSURE (Ref SECTION 8)**

## 5. Fire Fighting Measures

**Extinguishing Media:** Water sprays, Dry powder, CO2 or foam

**Exposure Hazards:** In case of fire, aside from the major combustion products Carbon Monoxide and Carbon Dioxide, other harmful gases and vapors may be formed.

**Fire Fighting Equipment:** Wear Self contained breathing apparatus, rubber boots, gloves and body suit

## 6. Accidental Release Measures

Avoid skin and eye contact. Prevent from entering sewer system, surface water or soil. For large amounts dike spilled product with liquid absorbing material and pump off. For small spills soak up and transfer to a suitable container. Wash area with water.

*Refer to section 5, 8 and 13 for Protective Measures and Disposal.*

## 7. Handling and Storage

Store in a cool dry area between 50F and 86F, away from direct sunlight, heat and sources of ignition – no smoking. Use in well ventilated area. Wash hands after contact.

## 8. Exposure Controls/ Personal Protection

### OCCUPATIONAL EXPOSURE LIMITS

**Respiratory:** Not required during normal use

**Ingestion:** Not during normal use

**Skin Protection:** Protective clothing should be worn to avoid skin contact, PVC or Rubber gloves

# Material Safety Data Sheet



**Eye Protection:** Safety Goggles

## 9. Physical/ Chemical Properties

<b>Appearance:</b>	Clear pale yellow liquid	<b>Odor:</b>	Weak
<b>Viscosity:</b>	Thick liquid	<b>Specific Gravity:</b>	1.15g/cm <sup>3</sup> at 68F
<b>Boiling Point/ Range:</b>	338° F	<b>Flammability:</b>	Will burn if involved in a fire
<b>Flash Point:</b>	>302° F	<b>Melting Point:</b>	N/A
<b>Auto Flammability:</b>	Above boiling point	<b>Explosive Properties:</b>	None
<b>Oxidizing Properties:</b>	None	<b>Vapor Pressure:</b>	N/A
<b>Evaporation Rate:</b>	N/A	<b>Solubility:</b>	Insoluble in water/ Soluble in with organic solvents
<b>PH:</b>	Neutral	<b>Partition Coefficient:</b>	No Data
<b>Di Electric Strength;</b>	No Data		

## 10. Stability and Reactivity

**Stability;** Stable  
**Materials to Avoid:** May react under considerable heat build up with amines and mercaptans. Acids  
**Hazardous Decomposition:** None  
**Hazardous Polymerizations:** None

## 11. Toxicological Information

**Oral:** LD 50 (rat) (95% in Acetone) 11.4g/kg  
**Inhalation:** Not during normal use  
**Eye:** Severe irritation  
**Skin:** Irritant. May cause sensitization

## 12. Ecological Information

Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

## 13. Disposal Considerations

Dispose of in accordance with local regulations

## 14. Transport Information

**UN No:** 3082    **Class:** 9    **P.G:** III    **Technical Name:** Environmentally hazardous substance, liquid, N.O.S. (epoxy resin)

## 15. Regulatory Information

**Labeling:** Irritant (Xi), Dangerous for the environment (N)

R Phrases (R36/38)	Irritating to eyes and skin
(R43)	May cause sensitization by skin contact
(R51/53)	Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment
S Phrases (S2)	Keep out of reach of children
(S24/25)	Avoid contact with skin and eyes
(S28)	After contact with skin wash immediately with plenty of soap and water
(S36/37/39)	Wear suitable protective clothing, gloves and eye/face protection
(S46)	If swallowed seek medical advice immediately and show this document or product label
(S61)	Avoid release to the environment.
Precautionary phrase (P5)	Contains epoxy constituents

**Regulations:** All components of this product are listed on the TSCA Inventory or are exempt from listing

# Material Safety Data Sheet



## 16. Other Information

Risk phrases used in section 3 and not previously mentioned:  
R38 Irritating to skin

**DATE OF PREPARATION: 1<sup>st</sup> December 2010**

The information contained within this document is furnished without warranty of any kind. Users should consider this data only as a supplement of other information gathered by them and make independent determinations of suitability and completeness of information from all sources to ensure proper use and disposal of these materials and the safety of employees and customers.